

AGRIMAX RT 600 - Teknik Özellikler

Description

AGRIMAX RT 600; çim saha, hasat ve yayma uygulamaları için ideal bir lastiktir. Geniş temas alanı sayesinde AGRIMAX RT 600, arazide mükemmel bir basınç dağılımı sağlayarak çim sahadaki hasarı azaltır ve toprağınızı korur. Yuvarlak omuz teknolojisi, güçlendirilmiş damak ve daha yüksek diş sayısı sayesinde mükemmel sabitleme ve çekiş sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver • Yayıcı • Traktör



Version	STANDARD
Type	TL
Tyre Size	800/65 R 32 (30.5L R 32)
LI/SS	181 A8/178 B

Dimensions US Standard

Usa code	94039302
Section Width (inch)	30.5
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	218.8
Rim Rec	DW 27 B
Rim Alt	DH 27 B ; DW 25 B
ECE	E4-106R-001429

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58	64
30	7000	8070	9890	10800	11870	12930	14000	15210	16530	-	-
25	7610	8760	10750	11740	12900	14050	15210	16530	18190	-	-
20	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	22160	24370	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 Cyc	-	12470	15940	17550	20390	22350	24370	26510	27420	28660	30860

Printed on 5/19/2024 11:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..