

AT 621 - Teknik Özellikler



Description

AT 621, tarımdaki tüm kazma ve yükleme işlemlerinde bekoloderler ve küçük yükleyiciler için uygundur. AT 621 lastiği, mükemmel kesilme ve kopma direnci ve daha yüksek dayanıklılık sağlayan ekstra derin bir sırta sahiptir. Ayrıca, bu BKT lastiği mükemmel dayanıklılık ve kendi kendini temizleme özellikleri sağlar. AT 621, çok farklı kullanıcı gereksinimlerini karşılamak için çeşitli versiyonlarda sunulmaktadır.

UM

US Standard

Construction

 BIAS

Machinery

Zirai: Küçük yükleyici • Bekoloder
Endüstriyel: Bekoloder • Yükleyici

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	148 A8

Dimensions US Standard

Usa code	94026258
Ply Rating	16
Section Width (inch)	12.1
Overall Diameter (inch)	38.9
Static Loaded Radius (inch)	17.1
Rolling Circumference (inch)	114.8
Rim Rec	W 9
Rim Alt	11.0
ECE	E11-106R-006957
TRA Code	R4

Load capacity (lbs)

mph / psi	71
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940
5 DW	6720
15 DW	5720
20 DW	5380
25 DW	4810

Printed on 5/18/2024 7:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..