

## EARTHMAX SR 31 - Teknik Özellikler



### Description

EARTHMAX SR 31 Tamamen Çelikten yapılmış radyal lastik belden kırmalı kaya kamyonları ve tekerlekli yükleyiciler için özel olarak tasarlanmıştır. Yönlü olmayan sert blok diş deseni çamurlu zeminde bile mükemmel çekiş ve manevra kabiliyetine imkan verirken çok katlı çelik kuşaklar olağanüstü güç ve denge sağlar. Üstün sürüş konforunun yanı sıra, EARTHMAX SR 31 kesilmeye ve ısıya dirençli özel bir sırt hamuru ile üretilir. Ayrıca, radyal gövde yapısı azalan yuvarlanma direnci sağlayarak önemli ölçüde yakıt tasarrufu sunar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Endüstriyel: Dozer • Yükleyici

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

## Dimensions US Standard

Usa code	94053742
TMPH	185
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Printed on 5/19/2024 6:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..