

## EARTHMAX SR 423 - Teknik Özellikler



### Description

EARTHMAX SR 423, taş ocağı, taşıma ve ağır kütük operasyonları dahil olmak üzere çeşitli uygulamalara uygun Tamamen Çelik bir radyal lastiktir. Yönsüz sırt deseni her türlü arazide mükemmel çekiş ve sabitleme sağlar. Lastik, ağır yüklerle çalışmak için idealdir. Güçlü Tamamen Çelik gövde, mükemmel aşınma ömrü ve takımalara ve delinmelere karşı direnç sunar. Güçlendirilmiş damağı ve omuz tasarımı, ağır hizmet koşullarında bile uzun lastik kullanım ömrüne katkıda bulunur.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Yoldışı: Yol ve yol dışı kamyon

Version	STANDARD
Type	TT
Tyre Size	11.00 R 20
LI/SS	152/149 J

## Dimensions US Standard

Usa code	94060672
Ply Rating	18
Overall Width (inch)	11.2
Overall Diameter (inch)	43.3
Rim Rec	8.00
Rim Alt	8.50

## Load capacity (lbs)

mph / psi	120
62 Load Single	7825
62 Load Dual	7165

Printed on 5/18/2024 6:18 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..