

FL 630 ULTRA - Teknik Özellikler



Description

FL 630 ULTRA; römorklar, tankerler ve yayıcılar için uygundur. Güçlendirilmiş damağı ve özel sırt tasarımı sayesinde her türlü arazide veya yolda çok amaçlı kullanım için ideal lastiktir. FL 630 ULTRA olağanüstü derecede daha az toprak sıkışması anlamına gelir.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Yayıcı • Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	165 D/176 A8

Dimensions US Standard

Usa code	94044955
Section Width (inch)	24.1
Overall Diameter (inch)	52.5
Static Loaded Radius (inch)	22.8
Rolling Circumference (inch)	160.2
Rim Rec	AG 20.00
ECE	E11-106R-006813

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
40	3640	4210	4770	5800	6700	7730	8750	9420	10450	11350
30	4410	5090	5780	7010	8110	9350	10590	11420	12650	13750
25	5020	5800	6580	7990	9240	10650	12060	13000	14410	15650
15	5740	6650	7540	9160	10590	12210	13820	14900	16510	17940
5	6550	7570	8590	10430	12060	13900	15740	16960	18800	20440

Printed on 5/22/2024 4:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..