

## FL 630 ULTRA - Teknik Özellikler



### Description

FL 630 ULTRA; römorklar, tankerler ve yayıcılar için uygundur. Güçlendirilmiş damağı ve özel sırt tasarımı sayesinde her türlü arazide veya yolda çok amaçlı kullanım için ideal lastiktir. FL 630 ULTRA olağanüstü derecede daha az toprak sıkışması anlamına gelir.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Yayıcı • Tanker • Römork

Version	STANDARD
Type	TL
Tyre Size	800/45 R 26.5
LI/SS	174 D/184 A8

## Dimensions International Standard

Section Width (mm)	828
Overall Diameter (mm)	1393
Static Loaded Radius (mm)	618
Rolling Circumference (mm)	4238
SRI (mm)	675
Rim Rec	AG 28.00
Rim Alt	AG 24.00
ECE	E11-106R-004074

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1955	2230	2505	3115	3540	4090	4640	5065	5555	6100
65	2145	2450	2750	3420	3890	4490	5095	5565	6100	6700
50	2600	2965	3330	4140	4705	5435	6165	6735	7385	8110
40	2880	3285	3690	4590	5220	6030	6840	7470	8190	9000
30	3240	3695	4150	5165	5870	6785	7695	8400	9210	10120
25	3390	3870	4345	5405	6145	7100	8050	8790	9640	10590
10	3860	4405	4945	6155	6995	8085	9170	10010	10975	12060

Printed on 5/22/2024 11:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..