

## FL 695 - Teknik Özellikler



### Description

FL 695, benzersiz merkezi blok sırt deseni ile inşaat ve tarım taşıma uygulamalarında kullanılan römorklar için özel olarak tasarlanmıştır. Güçlü gövdesi sayesinde FL 695 tüm koşullarda sabitliği koruyarak ağır yükler taşıyabilir ve derin sırtı yolda ve yol dışında uygulamalar esnasında optimum kendi kendini temizleme sağlar. Çoklu çelik kord katmanları, bu deseni delinmelere karşı güçlü kılar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Römork

Endüstriyel: Römork

|           |               |
|-----------|---------------|
| Version   | STEEL BELTED  |
| Type      | TL            |
| Tyre Size | 650/55 R 26.5 |
| LI/SS     | 178 D         |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94067886        |
| Section Width (inch)         | 24.8            |
| Overall Diameter (inch)      | 54.7            |
| Static Loaded Radius (inch)  | 24.8            |
| Rolling Circumference (inch) | 167             |
| Rim Rec                      | AG20.00         |
| Rim Alt                      | AG22.00         |
| ECE                          | E11-106R-007052 |

## Load capacity (lbs)

| mph / psi | 012  | 17   | 23    | 29    | 35    | 41    | 46    | 52    | 58    | 65    | 73    | 80    | 87    |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40        | --   | --   | --    | 7440  | 8600  | 9750  | 10750 | 11740 | 12900 | 13720 | 14550 | 15540 | 16530 |
| 30        | --   | --   | --    | 9010  | 10410 | 11810 | 13010 | 14210 | 15610 | 16610 | 17610 | 18820 | 20010 |
| 25        | --   | 7430 | 9230  | 10120 | 11690 | 13270 | 14620 | 15970 | 17550 | 18670 | 19800 | 21140 | 22490 |
| 20        | 6250 | 8240 | 10240 | 11240 | 12980 | 14740 | 16240 | 17740 | 19480 | 20720 | 21980 | 23480 | 24970 |
| 15        | 6540 | 8630 | 10710 | 11760 | 13590 | 15420 | 16990 | 18550 | 20380 | 21690 | 22990 | 24560 | 26120 |
| 10        | 6820 | 9010 | 11190 | 12280 | 14190 | 16100 | 17740 | 19380 | 21280 | 22650 | 24010 | 25650 | 27280 |
| 5         | 7440 | 9820 | 12200 | 13390 | 15480 | 17560 | 19340 | 21130 | 23210 | 24700 | 26190 | 27980 | 29760 |

Printed on 5/19/2024 4:04 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..