

MULTIMAX MP 522 - Teknik Özellikler



Description

MULTIMAX MP 522, tarımsal sanayi uygulamaları için geliştirilmiş çok amaçlı BKT lastiğidir. Teleskopik yükleyiciler ve küçük yükleyiciler gibi araçlarla gerçekleştirilen tüm kaldırma ve yükleme işlemleri için uygundur. Olağanüstü delinme direncinin yanı sıra sabitleme ve çekiş güçlü taraflardır. Özel hamuru sayesinde MULTIMAX MP 522, inanılmaz bir kesilme ve kopma direncine sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 480/80 R 26 IND |
| LI/SS | 167 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 479 |
| Overall Diameter (mm) | 1428 |
| Static Loaded Radius (mm) | 638 |
| Rolling Circumference (mm) | 4287 |
| SRI (mm) | 675 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 16 L |
| ECE | E11-106R-008146 |

Load capacity (Kg)

| km/h / bar | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | 2575 | 2815 | 3055 | 3295 | 3540 | 3780 | 4020 | 4260 | 4500 | 4740 | 4975 | 5215 | 5450 | - | - |
| 40 | 2575 | 2815 | 3055 | 3295 | 3540 | 3780 | 4020 | 4260 | 4500 | 4740 | 4975 | 5215 | 5450 | - | - |
| 30 | 2790 | 3045 | 3300 | 3550 | 3805 | 4060 | 4315 | 4565 | 4820 | 5075 | 5330 | 5580 | 5835 | - | - |
| 25 | 2890 | 3155 | 3420 | 3680 | 3945 | 4210 | 4475 | 4735 | 5000 | 5265 | 5525 | 5790 | 6050 | - | - |
| 10 Cyc. | 3200 | 3555 | 3910 | 4265 | 4620 | 4975 | 5330 | 5685 | 6040 | 6395 | 6750 | 7460 | 8175 | - | - |
| Static | 4900 | 5445 | 5990 | 6535 | 7080 | 7625 | 8170 | 8715 | 9260 | 9805 | 10350 | 10895 | 11445 | 11990 | 12535 |

Printed on 5/19/2024 12:44 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..