

MULTIMAX MP 527 - Teknik Özellikler



Description

MULTIMAX MP 527 tarımsal sanayi uygulamalarında teleskopik yükleyiciler ve küçük yükleyiciler için tasarlanmış çok amaçlı bir radyal lastiktir. Lastik, daha sert yüzeylerde bile mükemmel çekiş sağlayan bir blok diş deseni tasarımına sahiptir. Güçlü yanak, kaldırma modunda olağanüstü sabitleme sağlar. MULTIMAX MP 527, kesilme ve kopmaya karşı dirençli özel bir hamura ve uzun bir kullanım ömrüne sahiptir.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Küçük yükleyici • Teleskopik yükleyici
Endüstriyel: Küçük yükleyici • Teleskopik yükleyici

Version	STANDARD
Type	TL
Tyre Size	360/70 R 18 IND
LI/SS	142 A8/B

Dimensions International Standard

Section Width (mm)	360
Overall Diameter (mm)	969
Static Loaded Radius (mm)	439
Rolling Circumference (mm)	2887
SRI (mm)	475
Rim Rec	11
Rim Alt	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
ECE	E11-106R-002996

Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1275	1515	1725	1965	2200	2360	2650	-	-
40	1275	1515	1725	1965	2200	2360	2650	-	-
30	1365	1620	1850	2105	2360	2530	2840	-	-
25	1415	1680	1915	2180	2445	2625	2945	-	-
10 Cyc.	1555	1910	2250	2585	2945	3200	3620	3820	3975
Static	2380	2930	3445	3965	4515	4910	5550	5855	6095

Printed on 5/19/2024 5:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..