

## RIDEMAX FL 693 M - Teknik Özellikler



### Description

RIDEMAX FL 693 M, sıklıkla römork/tanker kamyonlarla yolda seyahat edenler için ideal bir radyal lastiktir. %75 yolda kullanım için tasarlanan RIDEMAX FL 693 M, hem konfor hem de kendi kendini temizleme özelliklerine öncelik vererek mükemmel yol performansı sağlar. Serinin D/E hız endeksi sınıfları, yolda seyahat ederken daha yüksek hızları temsil eder ve bu da önemli ölçüde zaman tasarrufu sağlar. Düşük yuvarlanma direnci daha az yakıt tüketimine katkıda bulunurken, güçlendirilmiş bir damak ve çelik kuşaklar daha fazla dayanıklılık sağlar.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Zirai: Tanker • Römork

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 400/45 R 17.5 |
| LI/SS     | 139 D         |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94066063        |
| Section Width (inch)         | 15.7            |
| Overall Diameter (inch)      | 31.5            |
| Static Loaded Radius (inch)  | 13.5            |
| Rolling Circumference (inch) | 92.8            |
| Rim Rec                      | 14.00           |
| ECE                          | E11-106R-006619 |

## Load capacity (lbs)

| mph / psi | 15   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 73   | 87   |
|-----------|------|------|------|------|------|------|------|------|------|------|------|
| 45        | 1220 | 1570 | 1960 | 2200 | 2550 | 2890 | 3170 | 3470 | 3810 | 4300 | 4880 |
| 40        | 1340 | 1720 | 2150 | 2410 | 2790 | 3160 | 3480 | 3810 | 4190 | 4720 | 5360 |
| 30        | 1630 | 2080 | 2600 | 2930 | 3380 | 3840 | 4220 | 4620 | 5070 | 5720 | 6490 |
| 25        | 1830 | 2340 | 2920 | 3280 | 3790 | 4300 | 4740 | 5180 | 5690 | 6420 | 7290 |
| 20        | 2030 | 2590 | 3240 | 3650 | 4210 | 4780 | 5270 | 5750 | 6320 | 7120 | 8090 |
| 15        | 2120 | 2710 | 3390 | 3810 | 4410 | 5000 | 5510 | 6020 | 6610 | 7450 | 8470 |
| 5         | 2410 | 3090 | 3860 | 4340 | 5020 | 5700 | 6270 | 6860 | 7530 | 8490 | 9640 |

Printed on 5/18/2024 9:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..