

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/70 R 28
LI/SS	140 D/143 A8

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1421
Static Loaded Radius (mm)	639
Rolling Circumference (mm)	4239
SRI (mm)	650
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-007610
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1375	1600	1825	2050	2275	2500
50	1445	1680	1920	2155	2390	2625
40	1510	1755	2005	2250	2495	2740
30	1585	1840	2100	2360	2620	2875
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1585	1840	2100	2360	2620	2875

Printed on 5/19/2024 1:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..