

# EARTHMAX SR 41 - Technical Specifications



## Description

EARTHMAX SR 41 is an All Steel radial tire perfect for Articulated Dump Trucks, Loaders and Dozers. Thanks to its all steel structure and special block pattern, EARTHMAX SR 41 provides excellent resistance against punctures and an extended service life. In addition to long working hours without downtime, the tire ensures extraordinary comfort. EARTHMAX SR 41 is also available in E4\*\*\*\* for Low Profile Dump Trucks (LPDT) used in underground haulage operations.

## UM

International Standard

## Construction

 RADIAL

## Machinery

OTR: Articulated Dump Truck (ADT) • Dozer • Loader • Low Profile Dump Truck (LPDT)

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	203 B/214 A2

## Dimensions International Standard

TKPH	240
Overall Width (mm)	880
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	837
Rolling Circumference (mm)	5680
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	**/*
TRA Code	E4/L4

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	14000	14250	15100	15500
10	18500	19500	20600	21200

Printed on 5/19/2024 1:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..