

# MULTIMAX MP 522 - Technical Specifications



## Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	380/75 R 20 IND (14.5 R 20)
LI/SS	148 A8/B

## Dimensions US Standard

Usa code	94045877
Section Width (inch)	15.1
Overall Diameter (inch)	42.3
Static Loaded Radius (inch)	19
Rolling Circumference (inch)	128
Rim Rec	W 12
Rim Alt	W 11 ; 11 ; 12
ECE	E11-106R-002963

## Load capacity (lbs)

mph / psi	23	29	35	41	46	52	55	58	61	64
30	3310	3900	4500	5080	5680	6310	6620	6940	-	-
25	3310	3900	4500	5080	5680	6310	6620	6940	-	-
20	3550	4190	4840	5490	6130	6780	7100	7430	-	-
15	3680	4350	5030	5700	6370	7040	7390	7720	-	-
5 Cyc.	4080	4980	5890	6790	7690	8600	9060	9510	9960	10430
Static	6260	7650	9040	10430	11820	13210	13900	14590	15290	15980

Printed on 5/18/2024 11:14 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..