

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	600/60 R 30.5
LI/SS	169 D

Dimensions US Standard

Usa code	94064335
Section Width (inch)	23.8
Overall Diameter (inch)	58.9
Static Loaded Radius (inch)	26.8
Rolling Circumference (inch)	177
Rim Rec	AG 20.00
Rim Alt	AG 18.00
ECE	E11-106R-006160

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	4250	4770	5940	6760	7800	8850	9670	10590	11640
40	4670	5250	6530	7420	8580	9720	10610	11640	12790
30	5650	6350	7900	8980	10370	11770	12850	14090	15480
25	6350	7130	8870	10100	11660	13230	14440	15830	17390
20	7050	7930	9850	11210	12940	14680	16040	17580	19310
15	7390	8290	10310	11730	13550	15370	16780	18400	20200
5	8410	9450	11740	13360	15420	17490	19110	20950	23010

Printed on 5/18/2024 6:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..