

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks.

Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction



Machinery

Agriculture: Tanker • Trailer

Version	HD
Туре	TL
Tyre Size	710/50 R 26.5
LI/SS	179 D

Dimensions US Standard

Usa code	94063673
Section Width (inch)	28.6
Overall Diameter (inch)	54.4
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	166
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-006008

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58	73	87
45	3890	4980	6230	7000	8090	9180	10120	11040	12140	13690	15550
40	4280	5470	6830	7690	8880	10090	11110	12140	13330	15030	17080
30	5170	6620	8280	9310	10760	12200	13450	14680	16140	18200	20680
25	5810	7440	9300	10460	12090	13710	15110	16500	18130	20460	23240
20	6460	8270	10330	11620	13430	15230	16780	18330	20130	22720	25800
15	6760	8640	10800	12160	14040	15930	17550	19170	21060	23760	26990
5	7690	9840	12300	13840	15990	18150	19990	21840	24000	27070	30750

Printed on 5/18/2024 7:25 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..