

AGRIMAX RT 600 - Technical Specifications

Description

AGRIMAX RT 600 is the ideal tire for grassland, harvesting and spreading applications. Thanks to its large contact area, AGRIMAX RT 600 ensures an excellent pressure distribution on the land reducing damage on grassland and protecting your soil. Thanks to its round shoulder technology, the reinforced bead and increased number of lugs, it guarantees great stability and traction.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • Spreader • Tractor



| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 750/65 R 26 |
| LI/SS | 171 A8/B |

Dimensions US Standard

| | |
|------------------------------|-------------------|
| Usa code | 94064311 |
| Section Width (inch) | 29.5 |
| Overall Diameter (inch) | 64.4 |
| Static Loaded Radius (inch) | 29 |
| Rolling Circumference (inch) | 196.3 |
| Rim Rec | DW 24 B |
| Rim Alt | DW 23 B ; DW 25 B |
| ECE | E11-106R-006182 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 6240 | 7190 | 8130 | 8820 | 9630 | 10710 | 11530 | 12610 | 13560 | - | - |
| 25 | 6240 | 7190 | 8130 | 8820 | 9630 | 10710 | 11530 | 12610 | 13560 | - | - |
| 20 | 6680 | 7700 | 8720 | 9450 | 10320 | 11470 | 12350 | 13500 | 14520 | - | - |
| 5 LT | 8370 | 9630 | 10910 | 11820 | 12910 | 14360 | 15450 | 16910 | 18180 | - | - |
| 5 HT | 6680 | 7700 | 8720 | 9450 | 10320 | 11470 | 12350 | 13500 | 14520 | - | - |
| 5 Cyc | - | 11550 | 13070 | 14160 | 15460 | 17220 | 18520 | 20260 | 21780 | 22130 | 23050 |

Printed on 5/19/2024 12:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..