

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great selfcleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction



₩ RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	320/70 R 20
LI/SS	113 A8/113 B

Dimensions US Standard

Usa code	94067558
Section Width (inch)	12.6
Overall Diameter (inch)	38.7
Static Loaded Radius (inch)	17.4
Rolling Circumference (inch)	114.8
Rim Rec	W10
Rim Alt	W9 ; W11
ECE	E11-106R-006944

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1400	1640	1860	2090	2320	2540
25	1400	1640	1860	2090	2320	2540
20	1500	1760	2000	2240	2490	2370
5 LT	1880	2190	2500	2800	3110	3410
5 HT	1500	1760	2000	2240	2490	2370

Printed on 6/1/2024 10:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..