

AGRIMAXFACTOR - Technical Specifications



Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	600/70 R 28
LI/SS	157 D/160 A8

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1551
Static Loaded Radius (mm)	714
Rolling Circumference (mm)	4667
SRI (mm)	725
Rim Rec	DW 20 B
Rim Alt	DW 18 L ; W 18 L
ECE	E11-106R-007655
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1940	2230	2560	2890	3220	3550	3880	4125
50	2040	2345	2690	3035	3385	3730	4075	4335
40	2125	2445	2805	3165	3530	3890	4250	4520
30	2235	2565	2945	3325	3705	4085	4465	4745
10 LT	2600	2990	3430	3875	4315	4760	5200	5530
10HT	2235	2565	2945	3325	3705	4085	4465	4745

Printed on 5/19/2024 1:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..