



AT 621 - Data Sheet



Description

AT 621 is suitable for backhoe loaders and compact loaders in all digging and loading operations in agriculture. The AT 621 tire features an extra deep tread which ensures great cut and chip resistance and higher durability. In addition, this BKT tire ensures great durability and self cleaning properties. AT 621 is available in several versions to meet the most differing user requirements.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Compact Loader • Backhoe Loader

Industrial: Backhoe Loader • Loader

SIZE	Version	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
33 X 12.5 - 15	STANDARD	R4				8	10.00 F SDC		318	851	394	2507	TT	E11-106R-005230
10.0/75 - 15.3	STANDARD		127 A6			10	9.0		267	780	373	2385	TL	E11-106R-007466
12.5/70 - 16	STANDARD	R4				14	10 LB		315	855	385	2584	TL	
12.5/70 - 16	STANDARD	R4				14	10 LB		315	855	385	2584	TT	
12.5/70 - 16	STANDARD	R4				8	10 LB		315	855	385	2584	TL	E11-106R-005295
9.00 - 16	INDUSTRIAL		137 A6			16	6.50 H	6.00 G	260	925	0	0	TT	E11-106R-005364
12.5/80 - 18	INDUSTRIAL HD	R4		135 A8	148 A8	16	W 9	11.0	308	987	434	2916	TL	E11-106R-005365
12.5/80 - 18	SPECIAL	R4		129 A8	142 A8	12	W 9	11.0	308	987	434	2916	TL	E11-106R-005329
12.5/80 - 18	STANDARD	R4		129 A8	142 A8	12	W 9	11.0	308	987	434	2916	TL	E11-106R-003388
12.5/80 - 18	STANDARD	R4		135 A8	148 A8	16	W 9	11.0	308	987	434	2916	TT	E11-106R-006957
12.5/80 - 18	STANDARD	R4		135 A8	148 A8	16	W 9	11.0	308	987	434	2916	TL	E11-106R-006957
12.5/80 - 18	STANDARD	R4		129 A8	142 A8	12	W 9	11.0	308	987	434	2916	TT	E11-106R-003388
15.5/60 - 18	STANDARD	R4	139 A2			10	W 13		394	940	428	2871	TL	E11-106R-003575
15.5/60 - 18	STANDARD	R4	141 A2			12	W 13		394	940	428	2871	TL	E11-106R-004651
15.5/70 - 18 (400/70 - 18)	STANDARD	R4				10	W 13		400	1030	474	3111	TL	E11-106R-005260
385/65 D 19.5	STANDARD		165 A2			16	11.75	12.25	390	1020	478	3136	TL	E11-106R-006419
12.5 - 20	STANDARD	R4				12	11.0		325	1040	0	0	TT	E11-106R-005293
17.5/65 - 20	STANDARD	R4				10	W 14 L		450	1090	490	3294	TL	E11-106R-005262
400/70 - 20	STANDARD	R4	152 B/168 A2			16	13	12 SDC ; 13 SDC ; 14	405	1090	494	3271	TL	
400/70 - 20	STANDARD	R4	149 A8				13	12 SDC ; 13 SDC ; 14	405	1090	494	3271	TL	E11-106R-005289
42 X 17 - 20	STANDARD	R4				10	14.00 TG SDC		432	1073	480	3198	TT	E11-106R-005294
16.9 - 24	INDUSTRIAL	R4	149 A8			12	DW 15 L	DW 14 L	450	1302	590	3906	TL	E11-106R-005374
17.5L - 24	STANDARD	R4	139 A8			8	DW 15 L	DW 14 L	450	1255	558	3752	TL	E11-106R-005267

19.5L - 24	STANDARD	R4	151 A8	12	DW 16 L		482	1305	587	3936	TL	E11-106R-005373
18.4 - 26	STANDARD	R4	156 A8	12	DW 16 L	DW 15 L	480	1425	649	4288	TL	E11-106R-003634
16.9 - 28	INDUSTRIAL	R4	154 A8	14	DW 15 L	DW 14 L	450	1410	639	4199	TL	E11-106R-007209
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1410	639	4199	TT	E11-106R-003635
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1410	639	4199	TL	E11-106R-003635
16.9 - 30	INDUSTRIAL	R4	153 A8	12	DW 15 L	DW 14 L	450	1460	670	4398	TL	E11-106R-005375

Printed on 5/18/2024 6:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..