

## EARTHMAX SR 45 M - Technical Specifications



### Description

EARTHMAX SR 45 M is an **All Steel** radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 M provides optimum traction and is ideal for operation in long hauls.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	24.00 R 35
LI/SS	209 B

## Dimensions International Standard

TKPH	333
Overall Width (mm)	664
Overall Diameter (mm)	2180
Static Loaded Radius (mm)	980
Rolling Circumference (mm)	6538
Rim Rec	17.00/3.5
Rim Alt	--
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Printed on 5/18/2024 4:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..