

EARTHMAX SR 45 M - Technical Specifications

Description

EARTHMAX SR 45 M is an **All Steel** radial tire specially designed for rigid haul trucks. EARTHMAX SR 45 M provides optimum traction and is ideal for operation in long hauls.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck



| | |
|-----------|-------------------------|
| Version | HEAT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 24.00 R 35 |
| LI/SS | 209 B |

Dimensions International Standard

| | |
|----------------------------|-----------|
| TKPH | 435 |
| Overall Width (mm) | 664 |
| Overall Diameter (mm) | 2180 |
| Static Loaded Radius (mm) | 980 |
| Rolling Circumference (mm) | 6538 |
| Rim Rec | 17.00/3.5 |
| Rim Alt | -- |
| Star Rating | ** |
| TRA Code | E4 |

Load capacity (Kg)

| km/h / bar | 5.00 | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 | 6.75 | 7.00 |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50 | 14000 | 14500 | 15500 | 16000 | 16500 | 17000 | 17500 | 18000 | 18500 |

Printed on 5/19/2024 3:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..