

EARTHMAX SR 55 - Technical Specifications



Description

EARTHMAX SR 55 is an All Steel radial tire specially designed for loaders, dozers and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability and traction.

UM

International Standard

Construction

🐺 RADIAL

Machinery

OTR: Dozer • Load Haul Dump (LHD) • Loader

| Version | CUT RESISTANT COMPOUND | | |
|-----------|------------------------|--|--|
| Туре | TL | | |
| Tyre Size | 26.5 R 25 | | |
| LI/SS | 214 A2 | | |

Dimensions International Standard

| Overall Width (mm) | 690 |
|----------------------------|-----------|
| Overall Diameter (mm) | 1786 |
| Static Loaded Radius (mm) | 810 |
| Rolling Circumference (mm) | 5375 |
| Rim Rec | 22.00/3.0 |
| Star Rating | *** |
| TRA Code | L5S |

Load capacity (Kg)

| km/h / bar | 6.75 | 7.00 | 7.25 | 7.50 | 7.75 | 8.00 |
|------------|-------|-------|-------|-------|-------|-------|
| 10 | 19000 | 19500 | 20000 | 20400 | 20800 | 21200 |

Printed on 5/19/2024 4:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..