

MULTIMAX MP 522 - Technical Specifications



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

Version	STANDARD
Type	TL
Tyre Size	400/80 R 24 IND (16.0/80 R 24)
LI/SS	162 A8/B

Dimensions US Standard

Usa code	94051397
Section Width (inch)	15.9
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	21.8
Rolling Circumference (inch)	148.7
Rim Rec	DW 13
Rim Alt	DW 12 ; DW 13 L ; DW 14 L
ECE	E11-106R-002965

Load capacity (lbs)

mph / psi	23	29	35	41	46	49	52	58	64	67	70	73	75	78
30	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
25	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
20	4380	5160	6060	6840	7630	7910	8310	9190	9950	10460	10710	11210	-	-
15	4540	5360	6280	7100	7910	8210	8620	9550	10340	10860	11110	11630	-	-
5 Cyc.	5030	6140	7230	8490	9590	10140	10680	11640	12890	13430	13950	14670	15010	15710
Static	7720	9410	11090	13010	14700	15540	16380	17860	19750	20590	21410	22500	23030	24080

Printed on 5/19/2024 3:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..