

# RIDEMAX IT 697 (M+S) - Technical Specifications



## Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	650/65 R 42 IND
LI/SS	171 D/176 A8

## Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1920
Static Loaded Radius (mm)	880
Rolling Circumference (mm)	5869
SRI (mm)	925
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E4-106R-002659

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2890	3565	4180	4860	5475	6150
50	3125	3855	4520	5250	5915	6645
40	3335	4120	4830	5610	6320	7100
30	3470	4280	5020	5830	6570	7380

Printed on 5/19/2024 9:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..