

RIDEMAX IT 697 (M+S) - Technical Specifications



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels. The tread design has been specially developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	710/70 R 38 IND
LI/SS	177D / 182A8

Dimensions US Standard

Usa code	94067084
Section Width (inch)	28.2
Overall Diameter (inch)	77.1
Static Loaded Radius (inch)	35.4
Rolling Circumference (inch)	234.3
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006762

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	8050	9820	10790	12720	14330	16090
30	8700	10600	11650	13730	15480	17380
25	9370	11430	12550	14800	16680	18740
20	9070	11780	12940	15270	17200	19310

Printed on 5/19/2024 5:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..