

V-FLEXA - Technical Specifications



Description

V-FLEXA is a radial tire specifically designed for agricultural trailers. It is a latest-generation flotation product featuring VF technology, which enables the transport of heavy loads both in the fields and on the road with an inflation pressure that is 30% less than that of a standard tire of the same size. Additional steel belts confer major resistance to the casing against impacts. Not only does V-FLEXA support heavy loads in full safety, it also avoids soil compaction thanks to perfect weight distribution. Moreover, V-FLEXA features great self-cleaning properties, durability as well as low rolling resistance.

UM

US Standard

Construction

🗱 RADIAL

Machinery

Agriculture: Trailer

Version	STEEL BELTED
Туре	TL
Tyre Size	VF 600/65 R 26.5
LI/SS	172 D

Dimensions US Standard

Usa code	94066056
Section Width (inch)	24.2
Overall Diameter (inch)	57.2
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	172.3
Rim Rec	AG20.00
ECE	E11-106R-006624

Load capacity (lbs)

mph / psi	12	17	23	29	35	41
45	5450	6960	8480	9620	11140	12650
40	5980	7640	9320	10560	12230	13890
30	7000	8960	10910	12360	14310	16260
25	7720	9870	12020	13630	15780	17930
5	9800	12540	15270	17320	20050	22790

Printed on 5/19/2024 5:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..