

AGRIMAX FORCE - Technische Daten



Description

AGRIMAX FORCE, das Spitzenprodukt von BKT, ist ein Radialreifen, der speziell zur Bodenbearbeitung, sowie Transport- und Ernteanwendungen mit Hochleistungstraktoren und Erntemaschinen entwickelt wurde. Dabei bietet er ein hervorragendes Arbeitspotenzial sowie effiziente Leistungen. Dank der IF-Technologie kann dieser Reifen schwere Lasten bei geringerem Reifendruck im Vergleich zu einem Standardreifen bei reduzierter Bodenverdichtung tragen. AGRIMAX FORCE hat einen verstärkten Wulst und wartet mit erstklassiger Traktion, ausgezeichneten Selbstreinigungseigenschaften und Kraftstoffersparnis neben einem komfortablen Fahrerlebnis auf.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Erntemaschine • Hochleistungstraktor

Version	STANDARD
Type	TL
Tyre Size	IF710/55 R 30 CFO
LI/SS	166 D

Dimensions US Standard

Usa code	94059904
Section Width (inch)	28.2
Overall Diameter (inch)	60.8
Static Loaded Radius (inch)	27
Rolling Circumference (inch)	181.7
Rim Rec	DW 25 B
ECE	E11-106R-005716
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	4880	5620	6470	7220	8070	8810	9880	10630
from 40 to 25	5370	6180	7120	7940	8870	9690	10860	11700
20	5580	6430	7400	8240	9230	10070	11290	12150
12	5790	6670	7680	8560	9580	10460	11720	12610
5	6810	7850	9040	10070	11260	12300	13780	14840
Upto 20 Cyc	6980	8040	9250	10320	11530	12590	14110	15190
Upto 10 Cyc	8310	9580	11030	12300	13750	15010	16820	18110
Upto 5 Cyc	9120	10500	12100	13490	15080	16470	18450	19860
5 HT	5580	6430	7400	8240	9230	10070	11290	12150

Printed on 19.05.2024 15:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..