

EARTHMAX SR 35 - Technische Daten



Description

Earthmax SR 35 ist ein radialer All Steel Niederquerschnittsreifen, der speziell für knickgelenkte Muldenkipper und Radlader entworfen wurde. Er eignet sich vortrefflich für Arbeiten, die hervorragende Traktion und Flotation erfordern. Dank der robusten Karkasse mit Stahlbändern verleiht der Reifen außergewöhnliche Dauerhaftigkeit sowie Widerstandsfähigkeit gegenüber Rissen und Stichen.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Knickgelenkter Muldenkipper • Planierer • Radlader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	750/65 R 25 (30/65 R 25)
LI/SS	209 A2

Dimensions US Standard

Usa code	94071340
Overall Width (inch)	29.1
Overall Diameter (inch)	63
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	189.1
Rim Rec	24.00/3.0
Rim Alt	22.00/3.0,25.00/3.0
Star Rating	**
TRA Code	L3

Load capacity (lbs)

mph / psi	73	76	80	83	87	91
5	34200	35300	36400	37500	38600	40800

Printed on 19.05.2024 04:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..