

## MULTIMAX MP 522 - Technische Daten



### Description

MULTIMAX MP 522 ist BKTs Mehrzweckreifen für agro-industrielle Anwendungen. Er eignet sich für alle Bagger- und Ladearbeiten mit Fahrzeugen wie Teleskopladern und Kompaktladern. Stabilität und hohe Traktion sind seine Stärken neben erstklassiger Durchstichfestigkeit. Dank der speziellen Gummimischung ist MULTIMAX MP 522 außergewöhnlich widerstandsfähig gegenüber Schnitten und Rissen.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Kompaktlader • Teleskoplader  
Industrie: Kompaktlader • Teleskoplader

|           |                                 |
|-----------|---------------------------------|
| Version   | STANDARD                        |
| Type      | TL                              |
| Tyre Size | 460/70 R 24 IND<br>(17.5L R 24) |
| LI/SS     | 159 A8/B                        |

## Dimensions US Standard

|                              |                   |
|------------------------------|-------------------|
| Usa code                     | 94031313          |
| Section Width (inch)         | 18.3              |
| Overall Diameter (inch)      | 49.2              |
| Static Loaded Radius (inch)  | 22.4              |
| Rolling Circumference (inch) | 148.3             |
| Rim Rec                      | DW 15 L           |
| Rim Alt                      | DW 14 L ; DW 16 L |
| ECE                          | E4-106R-002396    |

## Load capacity (lbs)

| mph / psi | 23   | 29    | 35    | 41    | 46    | 51    | 58    | 61    | 64    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 4630 | 5500  | 6270  | 7140  | 8010  | 8590  | 9650  | -     | -     |
| 25        | 4630 | 5500  | 6270  | 7140  | 8010  | 8590  | 9650  | -     | -     |
| 20        | 4960 | 5900  | 6720  | 7650  | 8580  | 9190  | 10330 | -     | -     |
| 15        | 5150 | 6120  | 6970  | 7940  | 8900  | 9550  | 10710 | -     | -     |
| 5 Cyc     | 5650 | 6960  | 8180  | 9410  | 10710 | 11650 | 13170 | 13900 | 14470 |
| Static    | 8660 | 10660 | 12540 | 14430 | 16420 | 17870 | 20190 | 21310 | 22190 |

Printed on 19.05.2024 18:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..