

MULTIMAX MP 522 - Technische Daten



Description

MULTIMAX MP 522 ist BKTs Mehrzweckreifen für agro-industrielle Anwendungen. Er eignet sich für alle Bagger- und Ladearbeiten mit Fahrzeugen wie Teleskopladern und Kompaktladern. Stabilität und hohe Traktion sind seine Stärken neben erstklassiger Durchstichfestigkeit. Dank der speziellen Gummimischung ist MULTIMAX MP 522 außergewöhnlich widerstandsfähig gegenüber Schnitten und Rissen.

UM

US Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Kompaktlader • Teleskoplader
Industrie: Kompaktlader • Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	480/80 R 26 IND
LI/SS	167 A8/B

Dimensions US Standard

Usa code	94073108
Section Width (inch)	18.9
Overall Diameter (inch)	56.2
Static Loaded Radius (inch)	25.1
Rolling Circumference (inch)	168.8
Rim Rec	DW 15 L
Rim Alt	DW 16 L
ECE	E11-106R-008146

Load capacity (lbs)

mph / psi	23	26	29	32	35	38	41	44	46	49	52	55	58	61	64
30	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
25	5680	6210	6730	7260	7800	8330	8860	9390	9920	10450	10970	11500	12010	-	-
20	6150	6710	7270	7830	8390	8950	9510	10060	10630	11190	11750	12300	12860	-	-
15	6370	6960	7540	8110	8700	9280	9870	10440	11020	11610	12180	12760	13340	-	-
5 Cvc.	7050	7840	8620	9400	10180	10970	11750	12530	13320	14100	14880	16450	18020	-	-
Static	10800	12000	13200	14410	15610	16810	18010	19210	20410	21620	22820	24020	25230	26430	27630

Printed on 19.05.2024 12:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..