

## MULTIMAX MP 527 - Technische Daten



### Description

MULTIMAX MP 527 ist ein radialer Mehrzweckreifen, der speziell für Teleskoplader und Kompaktlader in agro-industriellen Anwendungen entwickelt wurde. Der Reifen weist ein Blockmuster auf, das erstklassige Traktion auch auf härtesten Oberflächen bietet. Die robuste Flanke bietet hervorragende Stabilität im Hebemodus. MULTIMAX MP 527 zeichnet sich durch eine besonders schnitt- und reißfeste Gummimischung aus, die ein langes Betriebsleben gewährleistet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Kompaktlader • Teleskoplader  
Industrie: Kompaktlader • Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	400/70 R 20 IND (16.0/70 R 20)
LI/SS	149 A8/B

## Dimensions International Standard

Section Width (mm)	404
Overall Diameter (mm)	1068
Static Loaded Radius (mm)	494
Rolling Circumference (mm)	3282
SRI (mm)	525
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002656

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1560	1855	2115	2405	2700	2895	3250	-	-
40	1560	1855	2115	2405	2700	2895	3250	-	-
30	1675	1985	2265	2580	2890	3100	3480	-	-
25	1735	2060	2350	2675	3000	3215	3610	-	-
10 Cyc.	1905	2340	2755	3170	3610	3925	4440	4680	4875
Static	2920	3590	4225	4860	5535	6020	6805	7180	7475

Printed on 19.05.2024 09:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..