

## MULTIMAX MP 527 - Technische Daten



### Description

MULTIMAX MP 527 ist ein radialer Mehrzweckreifen, der speziell für Teleskoplader und Kompaktlader in agro-industriellen Anwendungen entwickelt wurde. Der Reifen weist ein Blockmuster auf, das erstklassige Traktion auch auf härtesten Oberflächen bietet. Die robuste Flanke bietet hervorragende Stabilität im Hebemodus. MULTIMAX MP 527 zeichnet sich durch eine besonders schnitt- und reißfeste Gummimischung aus, die ein langes Betriebsleben gewährleistet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Kompaktlader • Teleskoplader  
Industrie: Kompaktlader • Teleskoplader

Version	STANDARD
Type	TL
Tyre Size	460/70 R 24 IND (17.5L R 24)
LI/SS	159 A8/B

## Dimensions International Standard

Section Width (mm)	465
Overall Diameter (mm)	1254
Static Loaded Radius (mm)	574
Rolling Circumference (mm)	3801
SRI (mm)	600
Rim Rec	DW 15 L
Rim Alt	DW 14 L ; DW 16 L
ECE	E11-106R-002983

## Load capacity (Kg)

km/h / bar	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	2100	2495	2845	3240	3635	3895	4375	-	-
40	2100	2495	2845	3240	3635	3895	4375	-	-
30	2250	2675	3050	3470	3890	4170	4685	-	-
25	2335	2775	3160	3600	4035	4330	4860	-	-
10 Cyc.	2565	3155	3710	4270	4860	5285	5975	6305	6565
Static	3930	4835	5690	6545	7450	8105	9160	9665	10065

Printed on 19.05.2024 12:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..