

XL GRIP (BHL) - Technische Daten



Description

XL GRIP (BHL) wurde speziell für Baggerlader entwickelt, die Schwersteinsatz in den Anwendungen Graben, Planieren und Laden leisten. Das nicht richtungsgebundene Muster der Lauffläche sichert beste Traktion und Stabilität. Die spezielle Laufflächenmischung zeigt sich in hervorragender Schnitt- und Durchstoßfestigkeit und verlängert die Lebensdauer der Lauffläche.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Baggerlader

Version	INDUSTRIAL
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	285
Overall Diameter (mm)	1075
Static Loaded Radius (mm)	505
Rolling Circumference (mm)	3257
Rim Rec	7.5
Rim Alt	7.0

Load capacity (Kg)

km/h / bar	8.30	7.60
10	4480	-
40	-	3305

Printed on 19.05.2024 06:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..