

## EARTHMAX SR 41 - Especificaciones técnicas



### Description

EARTHMAX SR 41 es un neumático radial ideal para las palas cargadoras y los buldóceros en las aplicaciones de transporte, carga y empuje. Gracias a su estructura All Steel y al dibujo de bloques, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una duración prolongada. Además de muchas horas operativas sin paradas de la máquina, este neumático asegura un confort excepcional. EARTHMAX SR 41 (E-4/L-4) es un neumático radial All Steel ideal para volquetes articulados, palas cargadoras y excavadoras.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

Version	STANDARD COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B

## Dimensions International Standard

TKPH	235
Overall Width (mm)	678
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	775
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	E4

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	9500	9750	10300	10600	11200	11500

Printed on 19/05/2024 6:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..