

EARTHMAX SR 41 - Especificaciones técnicas



Description

EARTHMAX SR 41 es un neumático radial ideal para las palas cargadoras y los buldóceros en las aplicaciones de transporte, carga y empuje. Gracias a su estructura All Steel y al dibujo de bloques, EARTHMAX SR 41 ofrece una excelente resistencia a los pinchazos y una duración prolongada. Además de muchas horas operativas sin paradas de la máquina, este neumático asegura un confort excepcional. EARTHMAX SR 41 (E-4/L-4) es un neumático radial All Steel ideal para volquetes articulados, palas cargadoras y excavadoras.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Volquete articulado • Buldócer • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	875/65 R 29 (35/65 R 29)
LI/SS	203 B

Dimensions International Standard

TKPH	240
Overall Width (mm)	880
Overall Diameter (mm)	1865
Static Loaded Radius (mm)	837
Rolling Circumference (mm)	5680
Rim Rec	27.00/3.50
Rim Alt	27.00/3.0, 28.00/3.5
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
50	14000	14250	15100	15500

Printed on 19/05/2024 4:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..