

EARTHMAX SR 468 - Especificaciones técnicas



Description

EARTHMAX SR 468 es un neumático radial All Steel diseñado especialmente para camiones volquete rígidos. Su exclusivo diseño de la banda de rodadura con compuestos especiales la hace perfecta para condiciones mineras duras y rocosas. Sus tacos con ranuras circunferenciales y bloques entrelazados garantizan una disipación eficaz del calor. Además, el robusto hombro cuadrado ayuda a expulsar las piedras sueltas para proteger el neumático contra daños. EARTHMAX SR 468 se ha desarrollado con la tecnología de vanguardia de BKT para soportar cargas pesadas, ofrecer una mayor vida útil y proporcionar resistencia a los cortes y pinchazos de las rocas.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dúmper rígido

Version	STANDARD COMPOUND
Type	TL
Tyre Size	50/80 R 57
LI/SS	257 B

Dimensions International Standard

TKPH	1130
Overall Width (mm)	1205
Overall Diameter (mm)	3610
Static Loaded Radius (mm)	1597
Rolling Circumference (mm)	10870
Rim Rec	32.00/6.0
Rim Alt	29.00/6.0
Star Rating	**
TRA Code	E4

Load capacity (Kg)

km/h / bar	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	61500	63000	65000	67000	69000	71000	73000

Printed on 19/05/2024 11:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..