

EARTHMAX SR 49 M - Especificaciones técnicas



Description

EARTHMAX SR 49 M es un neumático radial All Steel con un dibujo no direccional particularmente proyectado para cargadoras LHD, volquetes de perfil bajo, palas cargadoras y buldóceres de que operan en las severas condiciones de los ambientes rocosos, principalmente en las minas subterráneas. EARTHMAX SR 49 M es ideal para las operaciones más duras que requieren una excepcional tracción y estabilidad excelente. La profundidad L-4 de la banda de rodadura y la fórmula especial UMS (underground mine service) de la mezcla, aseguran una mayor resistencia al desgaste, así como una excelente resistencia contra los cortes y los pinchazos causados por las rocas.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Buldócer • Cargadora LHD • Pala cargadora • Volquete de perfil bajo

Version	CUT RESISTANT COMPOUND (UMS)
Type	TL
Tyre Size	26.5 R 25

Dimensions International Standard

Overall Width (mm)	708
Overall Diameter (mm)	1782
Static Loaded Radius (mm)	801
Rolling Circumference (mm)	5297
Rim Rec	22.00/3.0
Star Rating	****
TRA Code	E4

Load capacity (Kg)

* "consult your servicing dealer or BKT representative for speed, load and pressure details."

Printed on 19/05/2024 7:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..