

FL 630 ULTRA - Especificaciones técnicas



Description

FL 630 ULTRA es un neumático de flotación idóneo para utilizarlo tanto en el campo como por carretera, con remolques, auto cisternas y pulverizadores. Gracias al talón reforzado y el dibujo particular de la banda de rodadura, el neumático es ideal para un uso polivalente en cualquier terreno y por carretera. FL 630 ULTRA es sinónimo de una compactación del suelo extraordinariamente reducida.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Esparcidor • Camión cisterna • Remolque

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 600/55 R 26.5 |
| LI/SS | 165 D/176 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94044955 |
| Section Width (inch) | 24.1 |
| Overall Diameter (inch) | 52.5 |
| Static Loaded Radius (inch) | 22.8 |
| Rolling Circumference (inch) | 160.2 |
| Rim Rec | AG 20.00 |
| ECE | E11-106R-006813 |

Load capacity (lbs)

| mph / psi | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 40 | 3640 | 4210 | 4770 | 5800 | 6700 | 7730 | 8750 | 9420 | 10450 | 11350 |
| 30 | 4410 | 5090 | 5780 | 7010 | 8110 | 9350 | 10590 | 11420 | 12650 | 13750 |
| 25 | 5020 | 5800 | 6580 | 7990 | 9240 | 10650 | 12060 | 13000 | 14410 | 15650 |
| 15 | 5740 | 6650 | 7540 | 9160 | 10590 | 12210 | 13820 | 14900 | 16510 | 17940 |
| 5 | 6550 | 7570 | 8590 | 10430 | 12060 | 13900 | 15740 | 16960 | 18800 | 20440 |

Printed on 19/05/2024 18:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..