

## MULTIMAX MP 527 - Especificaciones técnicas



### Description

MULTIMAX MP 527 es un neumático radial polivalente desarrollado para los elevadores telescópicos y las palas compactas que se utilizan en las aplicaciones agro-industriales. El neumático muestra un diseño de bloques de la banda de rodadura, garantizando una excelente tracción hasta en la superficie más dura. El robusto flanco del neumático asegura una extraordinaria estabilidad en modalidad de levantamiento. Además, MULTIMAX MP 527 está realizado con una mezcla particularmente resistente a los cortes y los desgarres, lo cual se traducen en una larga vida operativa del neumático.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cargadora compacta • Elevador telescópico  
Industrial: Cargadora compacta • Elevador telescópico

|           |                                 |
|-----------|---------------------------------|
| Version   | STANDARD                        |
| Type      | TL                              |
| Tyre Size | 460/70 R 24 IND<br>(17.5L R 24) |
| LI/SS     | 159 A8/B                        |

## Dimensions International Standard

|                            |                   |
|----------------------------|-------------------|
| Section Width (mm)         | 465               |
| Overall Diameter (mm)      | 1254              |
| Static Loaded Radius (mm)  | 574               |
| Rolling Circumference (mm) | 3801              |
| SRI (mm)                   | 600               |
| Rim Rec                    | DW 15 L           |
| Rim Alt                    | DW 14 L ; DW 16 L |
| ECE                        | E11-106R-002983   |

## Load capacity (Kg)

| km/h / bar | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.5  | 4.0  | 4.2  | 4.4   |
|------------|------|------|------|------|------|------|------|------|-------|
| 50         | 2100 | 2495 | 2845 | 3240 | 3635 | 3895 | 4375 | -    | -     |
| 40         | 2100 | 2495 | 2845 | 3240 | 3635 | 3895 | 4375 | -    | -     |
| 30         | 2250 | 2675 | 3050 | 3470 | 3890 | 4170 | 4685 | -    | -     |
| 25         | 2335 | 2775 | 3160 | 3600 | 4035 | 4330 | 4860 | -    | -     |
| 10 Cyc.    | 2565 | 3155 | 3710 | 4270 | 4860 | 5285 | 5975 | 6305 | 6565  |
| Static     | 3930 | 4835 | 5690 | 6545 | 7450 | 8105 | 9160 | 9665 | 10065 |

Printed on 19/05/2024 18:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..