

AGRIMAX FORCE - Fiche de données



Description

AGRIMAX FORCE, le produit phare de BKT, est un pneu radial spécialement conçu pour les applications de traitement du terrain, de transport et de récolte avec des tracteurs de grande puissance, auxquels il assure un maximum de performances et d'efficacité. Conçu avec la technologie IF, ce pneu supporte des charges lourdes avec de pressions de gonflage plus basses par rapport à un pneu standard. AGRIMAX FORCE se distingue de par une tringle renforcée en assurant une traction excellente, des excellentes qualités d'autonettoyage, une consommation réduite de carburant ainsi qu'une expérience confortable de conduite.;

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Moissonneuse • Tracteur de forte puissance

| SIZE | Version | USACode | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|--------------------|----------|----------|----------|-------|-------------------|---------------------------|------|------|------|-------|------|-----------------|
| IF 600/70 R 28 | STANDARD | 94044689 | R1W | 164 D | DW 21 B | DW 20 B | 23.7 | 61.1 | 27.3 | 183.2 | TL | E4-106R-000795 |
| IF 710/55 R 28 CFO | STANDARD | 94059690 | R1W | 165 D | DW 25 B | | 28.2 | 58.8 | 26.1 | 174.9 | TL | E11-106R-005498 |
| IF 600/70 R 30 CFO | SPECIAL | 94060047 | R1W | 165 D | DW 21 B ; DW 21 A | DW 20 A ; DW 20 B | 23.7 | 63.1 | 27.9 | 189 | TL | E11-106R-006495 |
| IF 600/70 R 30 CFO | STANDARD | 94045211 | R1W | 165 D | DW 21 B ; DW 21 A | DW 20 A ; DW 20 B | 23.7 | 63.1 | 27.9 | 189 | TL | E11-106R-006495 |
| IF 620/75 R 30 CFO | STANDARD | 94064717 | R1W | 169 D | DW 23 B | DW 21 B | 25.6 | 67 | 29.9 | 200.8 | TL | E11-106R-006496 |
| IF 710/60 R 30 CFO | STANDARD | 94038541 | R1W | 168 D | DW 25 B | | 27.9 | 63.5 | 28.1 | 189.5 | TL | E4-106R-001407 |
| IF710/55 R 30 CFO | STANDARD | 94059904 | R1W | 166 D | DW 25 B | | 28.2 | 60.8 | 27 | 181.7 | TL | E11-106R-005716 |
| IF 600/70 R 34 | STANDARD | 94045228 | R1W | 167 D | DW 21 B ; DW 21 A | DW 20 A ; DW 20 B | 23.7 | 67.1 | 29.8 | 199.6 | TL | E4-106R-001408 |
| IF 650/60 R 34 | STANDARD | 94063628 | R1W | 165 D | DW 23 B | DW 21 B | 25.6 | 64.7 | 29.4 | 195 | TL | E11-106R-006014 |
| IF 650/65 R 34 CFO | SPECIAL | 94060054 | R1W | 161 D | DW 23 B | DW 20 B | 25.6 | 67.3 | 30.1 | 199.9 | TL | E4-106R-001826 |
| IF 650/65 R 34 CFO | STANDARD | 94040742 | R1W | 161 D | DW 23 B | DW 20 B | 25.6 | 67.3 | 30.1 | 199.9 | TL | E4-106R-001826 |
| IF 710/55 R 34 CFO | STANDARD | 94059942 | R1W | 170 D | DW 25 B | | 28.2 | 64.8 | 29.4 | 195.4 | TL | E11-106R-005995 |
| IF 710/60 R 34 CFO | SPECIAL | 94060061 | R1W | 170 D | DW 25 B | | 27.9 | 67.6 | 30 | 201.8 | TL | E4-106R-001485 |
| IF 710/60 R 34 CFO | STANDARD | 94022229 | R1W | 170 D | DW 25 B | | 27.9 | 67.6 | 30 | 201.8 | TL | E4-106R-001485 |
| IF 710/75 R 34 CFO | STANDARD | 94053643 | R1W | 178 D | DW 25 B | DW 23 B | 28.2 | 75.9 | 34.3 | 227.4 | TL | E11-106R-003017 |
| IF 380/80 R 38 | STANDARD | 94062140 | R1W | 149 D | W 12 | W 11 ; W 13 | 15 | 61.9 | 28.5 | 188.7 | TL | E11-106R-005715 |
| IF 420/85 R 38 | STANDARD | 94058044 | R1W | 155 D | DW 14 L | DW 15 L | 16.5 | 65.7 | 30.7 | 197.5 | TL | E11-106R-004897 |
| IF 650/65 R 38 CFO | STANDARD | 94059225 | R1W | 169 D | DW 23 B | | 25.6 | 72 | 32.7 | 216.9 | TL | E11-106R-005103 |
| IF 650/75 R 38 CFO | STANDARD | 94069477 | R1W | 175 D | DW 23 B | DW 21 B | 25.6 | 76.4 | 34.1 | 228.4 | TL | E11-106R-007385 |
| IF 650/85 R 38 CFO | STANDARD | 94051236 | R1W | 179 D | DW 23 B | DW 20 B ; DW 21 B | 26.1 | 81.5 | 36.5 | 240.4 | TL | E4-106R-002649 |
| IF 710/60 R 38 | STANDARD | 94057511 | R1W | 172 D | DW 25 B | | 27.9 | 71.5 | 32 | 212.8 | TL | E11-106R-004754 |
| IF 800/70 R 38 CFO | STANDARD | 94055784 | R1W | 184 D | DW 27 B | DW 25 B, DW 28 B, DW 30 B | 31.3 | 82.1 | 36.3 | 243.5 | TL | E11-106R-006497 |
| IF 900/60 R 38 CFO | STANDARD | 94038749 | R1W | 184 D | DW 30 A ; DW 30 B | TW 31 B | 36.1 | 80.5 | 35.6 | 240.4 | TL | E11-106R-006493 |
| IF 650/85 R 42 CFO | STANDARD | 94046904 | R1W | 180 D | DW 23 B | | 25.6 | 85.6 | 38 | 252 | TL | E4-106R-001832 |
| IF 710/70 R 42 CFO | SPECIAL | 94060078 | R1W | 179 D | DW 25 B | DW 23 B | 28.2 | 81.1 | 36.2 | 242.8 | TL | E4-106R-001830 |
| IF 710/70 R 42 CFO | STANDARD | 94040926 | R1W | 179 D | DW 25 B | DW 23 B | 28.2 | 81.1 | 36.2 | 242.8 | TL | E4-106R-001830 |
| IF 710/75 R 42 CFO | SPECIAL | 94060085 | R1W | 181 D | DW 25 B | DW 23 B | 28.2 | 84 | 38.1 | 252.1 | TL | E11-106R-006490 |
| IF 710/75 R 42 CFO | STANDARD | 94046010 | R1W | 181 D | DW 25 B | DW 23 B | 28.2 | 84 | 38.1 | 252.1 | TL | E11-106R-006490 |
| IF 800/70 R 42 CFO | STANDARD | 94073658 | R1W | 192 D | DW 27 B | DW 25 B, DW 28 B, DW 30 B | 31.3 | 84.6 | 37.4 | 252 | TL | E11-106R-006481 |
| IF 800/70 R 42 | STANDARD | 94073641 | R1W | 186 | DW 27 B | DW 25 B, DW 28 B, DW | 31.3 | 84.6 | 37.4 | 252 | TL | E4-106R- |

| CFO | | | | D | 30 B | | | | 002650 | | | |
|---------------------------|----------|----------|-----|----------|---------|---------|------|------|--------|-------|----|-----------------|
| IF 900/50 R 42 CFO | STANDARD | 94058471 | R1W | 180 D | DW 30 B | TW 30 B | 34.7 | 77 | 34.3 | 229.5 | TL | E11-106R-006492 |
| IF 900/60 R 42 CFO | STANDARD | 94022236 | R1W | 186 D | DW 30 B | TW 30 B | 36.1 | 84.5 | 37.4 | 252.6 | TL | E11-106R-006494 |
| IF 750/75 R 46 CFO | STANDARD | 94058082 | R1W | 186 D | DW 25 B | | 29.2 | 90.3 | 40.6 | 267.8 | TL | E11-106R-006491 |
| IF 480/95 R 50 | STANDARD | 94058006 | R1W | 170 D | DW 16 B | | 18.9 | 85.4 | 39.4 | 258.8 | TL | E11-106R-004898 |

Printed on 19/05/2024 18:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..