

BK-LOADER 53 - Spécifications techniques



Description

BK-LOADER 53 est un pneu avec ceintures en aramide, développé pour les chargeurs dans les applications industrielles. Le dessin exclusif de la bande de roulement extra-profonde garantit une excellente stabilité latérale ainsi qu'une extraordinaire résistance à l'usure, aux coupures et aux crevaisons. BK-LOADER 53 se distingue par d'exceptionnelles propriétés d'autonettoyage, et par une traction et une adhérence optimales sur surfaces mouillées et sèches. Ce pneu est particulièrement adapté pour les opérations de recyclage.

UM

US Standard

Construction

 RADIAL

Machinery

Industriel: Chargeur

| | |
|-----------|---------------|
| Version | ARAMID BELTED |
| Type | TL |
| Tyre Size | 365/70 R 18 |
| LI/SS | 146A2/142A4 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94074143 |
| Section Width (inch) | 14.2 |
| Overall Diameter (inch) | 39 |
| Static Loaded Radius (inch) | 18 |
| Rolling Circumference (inch) | 118.8 |
| Rim Rec | 11 |

Load capacity (lbs)

| mph / psi | 22 | 29 | 36 | 44 | 51 | 58 | 65 | 73 | 80 |
|-----------|------|------|------|------|------|------|------|------|-------|
| 12 | 2060 | 2640 | 3100 | 3580 | 4090 | 4510 | 4980 | 5380 | 5850 |
| 5 | 2320 | 2980 | 3510 | 4040 | 4630 | 5100 | 5630 | 6090 | 6620 |
| STATIC | 3690 | 4740 | 5580 | 6420 | 7370 | 8110 | 8940 | 9680 | 10520 |

Printed on 19/05/2024 08:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..