

# EARTHMAX SR 31 - Spécifications techniques



## Description

EARTHMAX SR 31 est un pneu All Steel radial particulièrement conçu pour les tombereaux rigides et les chargeuses sur pneus. Les ceintures en acier multicouche assurent une force et une stabilité extraordinaires, tandis que le dessin non-directionnel rigide à blocs garantit d'excellentes traction et manœuvrabilité, même sur terrain boueux. EARTHMAX SR 31 se distingue non seulement par un confort de conduite exceptionnel, mais également par un mélange spécial de la bande de roulement, particulièrement résistante aux coupures et à la chaleur. La structure radiale de la carcasse offre de plus une faible résistance au roulement, et donc des économies de carburant non négligeables.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Industriel: Bulldozer • Chargeur

OTR: Tombereau articulé • Bulldozer • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/186 A2

## Dimensions International Standard

TKPH	170
Overall Width (mm)	540
Overall Diameter (mm)	1480
Static Loaded Radius (mm)	663
Rolling Circumference (mm)	4449
Rim Rec	17.00/2.0
Rim Alt	--
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	5800	6150	6500	6700	6900	7300
10	8000	8250	8750	9000	9500	-

Printed on 19/05/2024 13:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..