

EARTHMAX SR 44 - Spécifications techniques



Description

EARTHMAX SR 44 est un pneu radial **All Steel** (Tout Acier) adapté pour une série d'applications y compris les opérations dans les mines, les forêts ou de transport. Le dessin robuste de la bande de roulement E-4 assure une excellente traction et un grand confort pour l'opérateur. EARTHMAX SR 44 (E-4) est en mesure d'optimiser la productivité, quelle que soit votre opération.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Camion à benne basculante

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 10.00 R 20 |
| LI/SS | 146/143 G |

Dimensions International Standard

| | |
|----------------------------|--------------------|
| Ply Rating | 16 |
| Overall Width (mm) | 268 |
| Overall Diameter (mm) | 1075 |
| Static Loaded Radius (mm) | 505 |
| Rolling Circumference (mm) | 3200 |
| Rim Rec | 7.50 |
| Rim Alt | 7.0 ; 7.50VM ; 8.0 |
| ECE | E11-54R-0015908 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 8.3 |
| 90 | 3000 |

Printed on 19/05/2024 10:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..