

EARTHMAX SR 484 - Fiche de données



Description

L'EARTHMAX SR 484 PLUS est un pneu radial tout en acier spécialement conçu pour les camions à benne rigides destiné au transport en surface dans le secteur minier. Il est doté d'une conception de la bande de roulement unique E-3, avec un composé spécial qui assure une excellente protection sur des terrains difficiles et rocheux, ainsi qu'une traction accrue et d'excellentes propriétés d'auto-nettoyage. Sa construction tout acier avec des ceintures en acier multicouches offre une protection optimale contre les chocs, la fatigue et l'infiltration de roches, ce qui améliore le temps de disponibilité pour une productivité plus élevée. L'EARTHMAX SR 484 présente un épaulement en forme de carré, qui maximise le contact avec le sol pour une maniabilité et une stabilité optimales. Ce pneu BKT est spécialement conçu pour les vitesses plus élevées et les longs trajets.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Tombereau rigide

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
27.00 R 49	CUT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	525
27.00 R 49	HEAT RESISTANT COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	710
27.00 R 49	STANDARD COMPOUND	E3	**	223 B	19.50/4.0	--	735	2647	1193	8055	TL	610

Printed on 19/05/2024 07:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..