

## EARTHMAX SR 55 - Spécifications techniques



### Description

EARTHMAX SR 55 (L-55) est un pneu radial All Steel (Tout Acier) spécialement conçu pour les chargeuses, les bulldozers et les chargeurs-transporteurs qui opèrent dans les conditions les plus pénibles, comme les carrières et les mines et les chantiers de démolition. Grâce au dessin de la bande de roulement extra profonde et lisse, EARTHMAX SR 55 est capable d'atteindre des niveaux de productivité élevés, avec des temps d'arrêt machine inférieurs. Les opérateurs des machines en apprécieront aussi stabilité et traction excellentes.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Bulldozer • Chargeur-transporteur LHD • Chargeur

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	209 A2

## Dimensions US Standard

Usa code	94042128
Overall Width (inch)	27.2
Overall Diameter (inch)	70.3
Static Loaded Radius (inch)	31.9
Rolling Circumference (inch)	211.6
Rim Rec	22.00/3.0
Star Rating	**
TRA Code	L5S

## Load capacity (lbs)

mph / psi	76	80	83	87	91	94
5	34200	35300	36400	37500	39700	40800

Printed on 19/05/2024 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..