

FL 695 - Spécifications techniques



Description

Le FL 695 a été spécialement conçu pour les remorques dans les secteurs de la construction et du transport avec une bande de roulement unique à bloc central. Grâce à sa carcasse robuste, le FL 695 peut transporter de lourdes charges sans impact sur la stabilité quelles que soient les conditions, et sa bande de roulement profonde assure un auto-nettoyage optimal sur route et hors route. De multiples couches de câble d'acier renforcent cette sculpture contre les crevaisons.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Remorque
Industriel: Remorque

| | |
|-----------|---------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 650/55 R 26.5 |
| LI/SS | 178 D |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 630 |
| Overall Diameter (mm) | 1390 |
| Static Loaded Radius (mm) | 630 |
| Rolling Circumference (mm) | 4242 |
| SRI (mm) | 675 |
| Rim Rec | AG20.00 |
| Rim Alt | AG22.00 |
| ECE | E11-106R-007052 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.5 | 5.0 | 5.5 | 6.0 |
|------------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 65 | -- | -- | -- | 3375 | 3900 | 4425 | 4875 | 5325 | 5850 | 6225 | 6600 | 7050 | 7500 |
| 50 | -- | -- | -- | 4085 | 4720 | 5355 | 5900 | 6445 | 7080 | 7535 | 7990 | 8535 | 9075 |
| 40 | -- | 3370 | 4185 | 4590 | 5305 | 6020 | 6630 | 7245 | 7960 | 8470 | 8980 | 9590 | 10200 |
| 30 | 2835 | 3740 | 4645 | 5100 | 5890 | 6685 | 7365 | 8045 | 8835 | 9400 | 9970 | 10650 | 11325 |
| 25 | 2965 | 3915 | 4860 | 5335 | 6165 | 6995 | 7705 | 8415 | 9245 | 9840 | 10430 | 11140 | 11850 |
| 20 | 3095 | 4085 | 5075 | 5570 | 6435 | 7305 | 8045 | 8790 | 9655 | 10275 | 10890 | 11635 | 12375 |
| 10 | 3375 | 4455 | 5535 | 6075 | 7020 | 7965 | 8775 | 9585 | 10530 | 11205 | 11880 | 12690 | 13500 |

Printed on 19/05/2024 06:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..