

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	500/45 R 22.5
LI/SS	146 D/143 E

Dimensions US Standard

Usa code	94043767
Section Width (inch)	19.8
Overall Diameter (inch)	40.2
Static Loaded Radius (inch)	17.9
Rolling Circumference (inch)	122.6
Rim Rec	AG 16.00
ECE	E4-106R-000786

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2200	2470	3060	3490	4030	4570	4990	5470	6010
40	2410	2710	3370	3840	4430	5030	5490	6020	6610
30	2930	3280	4090	4650	5370	6080	6650	7290	8000
25	3300	3690	4600	5220	6030	6840	7470	8190	8990
15	3820	4290	5330	6060	7010	7950	8670	9510	10450
5	4350	4880	6070	6910	7980	9050	9890	10840	11900

Printed on 19/05/2024 11:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..