

RIDEMAX FL 693 M - Spécifications techniques



Description

RIDEMAX FL 693 M est le pneu idéal pour les applications de transports fréquents sur route avec des remorques/camions-citernes. Conçu pour l'utilisation 75% sur route, RIDEMAX FL 693 M présente des prestations excellentes sur route et priorise aussi le confort et les propriétés d'auto-nettoyage. L'indice de vitesse classe D/E de la gamme est synonyme de vitesse élevée sur la route avec un gain de temps considérable. La résistance au roulement réduite contribue à l'économie de carburant, tandis que la tringle renforcée et les ceintures en acier assurent une durabilité avancée.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Véhicule citerne • Remorque

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	163 D

Dimensions US Standard

Usa code	94069446
Section Width (inch)	19.8
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	21.4
Rolling Circumference (inch)	142.7
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E11-106R-007203

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	65	73	80	87
45	3250	4030	4410	5100	5780	6380	6960	7640	8140	8620	9210	9790
40	3550	4410	4840	5590	6350	6990	7640	8390	8930	9460	10110	10750
30	4300	5340	5860	6770	7690	8460	9240	10160	10810	11460	12240	13010
25	4830	6000	6590	7610	8640	9510	10390	11410	12140	12870	13750	14620
15	5620	6970	7650	8850	10040	11050	12070	13250	14110	14960	15980	16990
5	6400	7940	8710	10070	11420	12580	13750	15090	16060	17030	18190	19350

Printed on 19/05/2024 14:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..