

XL GRIP (BHL) - Spécifications techniques



Description

XL GRIP (BHL) a été particulièrement conçu pour les chargeuses pelleteuses utilisées dans les opérations pénibles lors des applications d'excavation, nivellement et chargement. Le dessin non directionnel de la bande de roulement assure d'excellentes traction et stabilité. Le mélange spécial de la bande de roulement confère une excellente résistance aux coupures et déchirures et allonge la vie du pneu.

UM

International Standard

Construction

 BIAS

Machinery

Industriel: Chargeuse-pelleteuse

| | |
|-----------|--------------|
| Version | STEEL BELTED |
| Type | TT |
| Tyre Size | 10.00 - 20 |

Dimensions International Standard

| | |
|----------------------------|------|
| Ply Rating | 18 |
| Overall Width (mm) | 285 |
| Overall Diameter (mm) | 1075 |
| Static Loaded Radius (mm) | 505 |
| Rolling Circumference (mm) | 3257 |
| Rim Rec | 7.5 |
| Rim Alt | 7.0 |

Load capacity (Kg)

| km/h / bar | 8.30 | 7.60 |
|------------|------|------|
| 10 | 4480 | - |
| 40 | - | 3305 |

Printed on 19/05/2024 08:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..