

AGRIMAX FORCE - Technical Specifications



Description

AGRIMAX FORCE, the high-end product of BKT, is a radial tire specially designed for soil tillage, haulage and harvesting applications with high-power tractors and harvesters, ensuring top performance and efficiency. Thanks to its IF technology, this tire can carry heavy loads with a lower inflating pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides enhanced traction, top self-cleaning properties and fuel economy in addition to a comfortable riding experience.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester • High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	IF 650/85 R 42 CFO
LI/SS	180 D

Dimensions US Standard

Usa code	94046904
Section Width (inch)	25.6
Overall Diameter (inch)	85.6
Static Loaded Radius (inch)	38
Rolling Circumference (inch)	252
Rim Rec	DW 23 B
ECE	E4-106R-001832
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	7540	8660	9940	11230	12510	13800	15080	16050
From 40 to 25	8290	9520	10930	12350	13760	15170	16580	17600
20	8620	9900	11360	12830	14300	15770	17240	18340
12	8950	10280	11810	13330	14850	16380	17900	19050
5	10530	12090	13880	15670	17460	19260	21050	22400
Upto 20 Cyc	10770	12380	14210	16050	17880	19710	21550	22930
Upto 10 Cyc	12840	14760	16940	19140	21320	23500	25690	27340
Upto 5 Cyc	14090	16180	18580	20990	23380	25780	28170	29980
5 HT	8620	9900	11360	12830	14300	15770	17240	18340

Printed on 19/05/2024 10:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..